

Play equipment which
can be easily adapted
for children with
physical disabilities.



JPX26


Piccolo range

PICCOLO is a fairytale world full of fun activities, ideal for a small play area.

+ Ideas: a play equipment system with a highly modular structure designed for young children from **2 to 5 years**.

+ Design: the PICCOLO range is available with 3 different themes: "Fantastic", "Forensic" and "Cartoon" to stimulate youngsters' imagination.

+ Fun: with over 120 available activities, PICCOLO enables original configurations to be created to delight our young adventurers!



Identification

Catalogue	Play Equipment
Range	Piccolo
Universe/Theme	Fantastic
Page	48

Recreational characteristics

Age group	2-5 years
Number of activities	21

Dimensional characteristics

Equipment dimensions (LxVxH)	9127x5880x3400 mm
Maximum free-fall height	2 m
Max. floor height	1.2 m
Overall dimensions of impact area	12549x9356 mm
Total impact area in m²	68.5

Materials

Frame/Structure	Galvanised, painted steel
Railing/Trim	HPL
Assembly	Powder coated cast aluminium
Other materials used	Rotation moulded thermoplastic/stainless steel
Slide*	Rotation moulded thermoplastic
Slide (2)*	HPL - Stainless steel


Standards (tested by an independent laboratory)

NF-EN 1176 Version 2008	Yes
-------------------------	-----

Installation

Delivery	Kit
Foundation	Level: 0 or -0.40 m : 26 blocks or concrete slab

*The slides are available in 3 versions (Steel/Stainless Steel, HPL/Stainless Steel, Thermoplastic).



SAFETY AREA : 68,5 m²

View from above and cross-sectional view (scale 1:100)



Piccolo range



+ FRAME/STRUCTURE

Robustness tested under 1 tons!

Example: To ensure exceptional robustness during intensive use and to offer a high safety factor, the PICCOLO triangular flooring (1200x1200x1200 mm) has been tested under 1 ton!



+ FLOORS/COVERING

HPL floors and panels

Multi-coloured HPL panels specially designed for HUSSON: high-pressure laminate, extremely wear-resistant (thickness 15 mm), rot-proof, not readily flammable, volume-dyed solid material.

The flooring is made from anti-slip perforated HPL to facilitate maintenance.



+ THERMOPLASTIC COMPONENTS

Rotation moulded thermoplastic components

The complex-shaped components are made using the rotational moulding technique. For optimum robustness, HUSSON only uses volume-dyed, extremely thick, easy maintenance, top-of-the-range HDPE (High Density Polyethylene) type material.



+ SURFACE COATING

Extremely resistant double coating

All our steel sections feature double-surface coating:

- Treatment 1: hot-dip galvanisation after manufacture (on the inside and outside of the tubes)
- Treatment 2: powder coating (powder paint, cured in an oven)



+ ASSEMBLY

Exclusive assembly system

- Clips and bearings manufactured in injected cast aluminium.
- Special anti-loose, vandal-resistant stainless steel bolts (with exclusive HUSSON tool).
- Use of stainless steel and an exclusive* assembly system on all of HUSSON's ranges enables easy and cost-effective maintenance.
- Improved robustness thanks to a double-clamping system.



+ NETTING

Husson's exclusive feature

Our steel core climbing netting is coated with a substantial colour polyamide sheath.



+ SAFETY

Safety that surpasses current standards

The PICCOLO play equipment is designed in accordance with the new European standards EN 1176 version 2008 and Decree no. 94-699.

Compliance with standards is guaranteed by tests and certification carried out by an independent test laboratory.

Designed with utmost concern for safety, the PICCOLO play equipment often exceeds current standards and regulations such as for:

- The robustness of its frames
- Its fall protection connection railings
- Its ergonomic access points and bridges, etc.



+ GUARANTEE

Long-term 10 year guarantee

- Guaranteed parts: metal frame (posts and assembly parts), HPL panels, flooring.
- For HUSSON's guarantee application conditions: see HUSSON's general terms and conditions of sale (on the last pages of the current price list).

*Patented exclusive system